

PTZ OPTICS PT-Broadcaster-L



PTZ OPTICS

SKU: PT-Broadcaster-L

Broadcast PTZ Camera Controller

The PTZ Optics PT-Broadcaster-L is a portable broadcast camera control system that supports Sony, Panasonic, Canon and other broadcast-handheld camcorders providing remote control. Achieve full speed PTZ Control with intelligent soft start and stop control. Feel safe with our built-in voltage control regulator for power protection.

KEY FEATURES

- Supports Sony, Panasonic, Canon Cameras
- Supports VISCA, Pelco P & Pelco D control protocols
- Full speed PTZ Control, with intelligent start/stop
- Up to 255 Presets
- Supports Ceiling Mounting

WHAT'S IN THE BOX

- Portable Camera Controller
- Power Supply
- Instruction Manual
- Connection Cables

Supports Camera Types

Supported Camera Types:

SONY PXW-X160, SONY PXW-Z100, SONY PXW-X180, SONY HXR-NX3, SONY HXR-NX5C, SONY HXR-NX70C, SONY HXR-MC2500, SONY HXR-MC1500C, SONY NEX-FS700RH, SONY PXW-FS7, JVC GY-HM850E, JVC GY-HM890E, JVC GY-HM600EC, JVC GY-HM600KX, JVC GY-HM650EC, JVC GY-HM750E (Requires DIN 6 to 2.5mm LANC jack converter), JVC GY-HM790E (Requires DIN 6 to 2.5mm LANC jack converter), CANON XF305, CANON XF300, CANON XF205, CANON XF200, CANON XF105, CANON XF100, Most models with with the remote lens control jack (2.5mm LANC)

Supported Controllers:

VISCA Protocol Controller, Pelco-P/D Controller

Pan & Tilt Movement

| | |
|----------------|--|
| Rotation Range | 340° |
| Rotation Speed | Level: .01 ~25°/S; Vertical: 0.1~20°/S |
| Presets | 255 Presets |

Additional Support

| | |
|-----------------------|--------------------------------------|
| Remote Switch | Supported |
| Power Supply Module | Supported |
| External Power Supply | Supported |
| Decoder | Built-in higher performance de-coder |
| Controller Distance | 1200 Meters Max |
| Max Load | Side Load: 11lbs Top Load: 6lbs |
| Control Interface | RS-485, RS-422 |

Electrical Index

| | |
|---------------|------------------------------|
| Power Supply | 15W Consumption (w/o camera) |
| Input Voltage | AC/DC 15~24 (3 A) |

Physical Specifications

| | |
|------------|---------------------|
| Dimensions | 6.2" x 5.9" x 10.6" |
| Weight | 8.8 lbs. |